

Tubs, Showers, Sinks & Countertops

KITCHEN & BATH *Sealant*

Resistant to Water and Mildew / Will Not Shrink or Discolor / Permanently Seals

Titebond® Kitchen & Bath Sealant is a non-reactive, high-performance, modified acrylic formula designed to permanently seal high-moisture areas found in kitchens and baths. This flexible sealant offers strong, watertight adhesion and is safe for food preparation areas when fully cured. This mildew-resistant sealant will not discolor over time and offers a durable water, humidity and stain resistant seal.

STAIN & DIRT RESISTANT

Ideal For

Tubs / Showers / Sinks / Countertops

Seals

Vinyl / Ceramic Tile / Porcelain / Plastic / Painted Surfaces / Aluminum / Glass / Marble / Brick / Wood / Most Common Building Materials

Ultra Low VOC

VOC-compliant in all 50 states

Joint Movement

Remains flexible

Paintable

May be painted with a water-based (latex-based) paint 2-4 hours after application

Wide Temperature Application Range

40°F - 120°F



Titebond®
THE PRO'S ADVANTAGE

Ordering/Sku Information

Size/Color	Part Number	UPC	Case UPC	Weight	Units Per Package	Packages Per Pallet
10.1 Oz. Cartridge / White	1701	037083017017	10037083017014	12.37 lbs.	12	108
10.1 Oz. Cartridge / Clear	1711	037083017113	10037083017110	10.50 lbs.	12	108

Physical & Chemical Properties

- **Type:** Modified acrylic
- **Calculated VOC:**
 - **White & Clear:** <50 g/L (<1.5%)
- **Weight per gallon:**
 - **White:** 11.23 lbs.
 - **Clear:** 8.8 lbs.
- **Tooling time:** 10-15 minutes
- **Full cure:** 3-7 days*
- **Freeze thaw stability:** Stable
- **Flashpoint:** Solvent free/Not applicable
- **Application temperature:** Above 40°F (4°C)
- **Joint movement capability:** Flexible
- **Storage life:** 24 months in a dry location at or below 75°F
- **Coverage:** 31 linear ft. at a 1/4" bead.
- **Paintable:** 4-6 hours
- **Solids:**
 - **White:** 72%
 - **Clear:** 60%
- **Cleanup:** Clean uncured material with water. After curing, excess sealant must be cut or scraped away.

* Cure will be affected by joint size, configuration and environmental conditions.

Specifications

Complies with the following requirements:

- **White:** ASTM C834 Type OP Grade 0°C; FDA 21-CFR-177.2600
- **Clear:** ASTM C834 Type C Grade NF; FDA 21-CFR-177.2600

Application

Titebond® Kitchen & Bath Sealant comes ready to use. Surfaces must be clean and free of any material that may prevent adequate adhesion. Properly designed joint not to exceed 1/2" in depth. Cut tip at 45° angle for 1/8" to 1/2" bead and place in professional cartridge gun. Force sealant into clean joint. If necessary, smooth bead immediately. It is the sole responsibility of the user to thoroughly test any proposed use with all substrates to determine project suitability.

Limitations

Not designed for continuous submersion or use below the waterline. Air, sealant and surface temperature should be above 40°F. Allow at least 24 hours before exposing to water. Cure time is dependent upon ambient conditions including temperature and humidity. The sealant should be dry to the touch and ready to paint in 4-6 hours with a water-based (latex-based) paint. For other paint types, a compatibility test is recommended. It is highly recommended to use backing material. For best results, store in a dry location at or below 75°F. For questions, please call our Help Line 1.800.347.4583 or visit us at Titebond.com. **NOTE:** Titebond Kitchen & Bath Clear (1711) will be white during application, but will turn clear within 7-14 days, depending on temperature, humidity and bead size.

Liability is limited to product replacement only.

Visit Titebond.com for the most up-to-date product information.

Franklin International



Columbus, Ohio 43207 614.443.0241 Technical Service 1.800.347.4583 © 2020 00430_4826LN FF1014

